

## Brief Introduction of ZX60 Series IP Phone System

The all-in-one ZX60 series of IP phone system can not only provide the basic features of traditional PBX, but also advanced features such as visual voice mail, music on hold and auto attendant, etc. With Zycoo VoIP solutions, SMEs can take advantage of the VoIP services and quickly deploy VoIP networks to connect with multiple branch locations over the Internet without any change on the current equipment or dial plan.



ZYCOO ZX60 Series IP phone system product line includes **ZX60-A32**, **ZX60-A64**, which has different interface in the following table.

	Model	FXS	FXO
ZX60-A32	A32284	28	4
	A32248	24	8
ZX60-A64	A32604	60	4
	A32568	56	8

Key Features	Up to 64 Analog extensions		
	30 SIP registers		
	FXO Life line to FXS		
	Multiple Languages		
	DID(Direct Inward Dialing Number)		
	Support SKYPE for SIP		
	Call Monitoring		
Basic Features	Codec: G.711-Ulaw,G.711-Alaw,G.726,G.729		
	GSM,SPEEX,H.261,H.263,H.263+,H.264		
	Call Hold/Forward/Transfer/Waiting/Parking		
	Call Paging and Intercom		
	Call Queue		
	Caller ID  Music On Hold  DISA(Direct Inward System Access)		
	Flexible Dial Plan		
	Ring Group		
	Conference Room		
	Call Logs		
	BLF(Busy Lamp Field) Configuration By web Built-in SIP/IAX2 server		
	Build-in voice mail server		
	System Backup and Restore		
	Echo Cancelation/VAD		
	Support Static/DHCP/PPPOE		
	VPN Client(Support N2N)		
	DDNS Client(Support Dyndns.org)		
	Support NTP(Network Time Protocol)		
Hardware	32 bit embedded RISC DSP		
	1G Onboard Nand Flash		
	128M SDRAM		
Package size	L: 560mm × W: 455mm × H: 145mm		
Weight	5.7 Kg		
Certificate	(€ TBR21 F© TOHS		
Environmental	Temperature: -10°C-45°C		
requirements	Storage temperature: -30°C-65°C		
	Humidity: 10-80% no dew		
	Power: AC100~240V		

## SOHO or Small and medium businesses



